

3M DBI-SALA Salalift II Winch with 18m of Galvanized Steel Cable, Mounting Bracket and Winch Bag

Model : 8102001



Product Details

- Manually operated winch
- 18 m of 6mm galvanised steel wire rope
- 6:1 gear ratio mechanical advantage
- Quick mount bracket
- Free-wheel mode
- Built-in fall protection
- Overload clutch
- Durable corrosion resistant construction
- Level wind system
- Reserve lifeline retention system
- Swiveling snap hook with impact indicator
- Equipped with 3M Connected Safety ID (CSID)
- Order tripod or davit rescue system separately

Winch with 18m of 6 mm galvanised steel wire rope and swivel snap hook, mounting bracket and carrying bag.

When it comes to confined space entry/rescue, it is essential that equipment operates perfectly and quickly. DBI-SALA has an extensive line of rescue and retrieval systems with decades of proven field service. Safety engineers and site directors trust DBI-SALA for the type of high quality, rugged systems that will ensure top performance when it is needed the most. Our mechanical systems are legendary and have decades of proven field service and have operated flawlessly in some of the most demanding jobsites around the globe. The mechanical device is one of the most critical parts of the rescue system. It provides the means to retrieve an incapacitated worker to safety. Lifeline type and length are just a few of the options. In some situations, a secondary or back-up system is required.

Specifications	
Brands	DBI-SALA
Cable Length (metric)	18.288 Metre
Cable Material	Galvanized Steel
Carabiner/Hook Material	Zinc Plated Steel
Case Quantity	1
Colour	Anodised Yellow, Black
Connected Safety ID Equipped	Yes
Install Type	Portable
Product Operation	Manual
Product Series	Salalift II
Product Type	Winch
Recommended Industry	Construction, General Industrial, Mining, Oil & Gas, Transportation, Utilities
Weight Capacity (Metric)	159 kg

