Find the fit for your industry and application.

In our dedicated pursuit to help workers stay safe at heights, we have developed performance optimizations for a variety of industries and working applications.


Find the fit for your industry and application with our NEW 3M[™] DBI-SALA[®] ExoFit[™] X-Style Harnesses.


Backed by science to fit your body. Our new quick-connect chest buckle, simplified harness sizing ranges, and leg straps have been designed with you in mind. No matter the season, wardrobe or body shape, the 3M™ DBI-SALA® ExoFit™ X300 Comfort X-Style Safety Harness will help ensure you select a harness that fits your body securely.





General Industry

Equipped with lightweight aluminum dorsal D-ring (automatic stand-up D-ring design enables easier connections).











Construction

Distribution

Weight

Wind Energy

Equipped with front Equipped with robust construction hip pad D-ring for climbing, and lightweight back side D-rings and seat sling for comfortable weight and fatigue positioning at height. from shoulder area.



Telecommunications

Equipped with front D-ring for climbing, side D-rings and seat sling for comfortable positioning at height.

Featured X300 Harnes

2X-Large 1113194

1113190

1113191

1113192

1113193

Small

Medium

Large

X-Large



X-Style General Industry



X-Style Construction



X-Style **General Industry** Climbina*



X-Style Climbing/ **Positoning** (Wind Energy)*



X-Style **Tower Climbing** (Telecommunications)*

Equipped with contoured form-fitting chest configuration to don easily in 'X' shape. X-Style harness buckle contours to your body, providing an optimal central connection. New horizontal leg straps complement the range of motion workers require on the jobsite.

Featured X300 Harness		Featured X300 Harness		
X-Small/ Small	1403198		X-Small/ Small	1403207
Medium/ Large	1403199		Medium/ Large	1403208
X-Large/ 2X-Large	1403200		X-Large/ 2X-Large	1403209

Featured X300 Harness					
X-Small/ Small	1403201				
Medium/ Large	1403202				
X-Large/ 2X-Large	1403203				
	X-Small/ Small Medium/ Large X-Large/				

Featured X	Featured X300 Harness		
X-Small/ Small	1403213		
Medium/ Large	1403214		
X-Large/ 2X-Large	1403215		

ss	Featured X	Featured X300 Harness		
3	X-Small/ Small	1403210		
1	Medium/ Large	1403211		
5	X-Large/ 2X-Large	1403212		

*Optimize your vertical climbing applications with our 3M™ DBI-SALA® ExoFit™ X300 Comfort X-Style Climbing Safety Harness styles equipped with centered front D-ring-coming soon. Contact your local 3M Fall Protection specialist to learn more.



3833 SALA Way Red Wing, MN 55066 USA

Phone 800.328.6146 Email 3Mfallprotection@mmm.com Web 3M.com/FallProtection


3M, DBI-SALA, ExoFit, and Scotchlite are trademarks of 3M © 3M 2022. All rights reserved.



3M DBI-SALA ExoFit Safety Harnesses Brochure v4-1.indd 1-3

Designed for ultimate productivity and performance.

Wherever your work takes you, staying comfortably fitted in your safety harness is critical. Precision-tuned for performance and productivity, our new line of 3M™ DBI-SALA® ExoFit™ X-Series Harnesses change the way you work and redefine what you should expect from a safety harness.



3M™ DBI-SALA® **ExoFit™ X-Series** Harnesses come equipped with these standard harness features:

Revolving Torso Adjusters*

 Patented buckles lock webbing into place to maintain a safe and comfortable fit.

Personal SRL Adapter

 Confidently connect personal SRLs to the harness with ease.

Anti-Slide Dorsal D-Ring Pad

• Greatly reduces dorsal D-ring slide and allows for adjustment to help ensure a proper and safe fit.

Suspension Trauma Relief Straps*

• Integrated low-profile design between harness webbing.

Auto-Resetting Lanyard Keepers*

• Fast and easy parking of snap hooks and carabiners.

Comfort Padding

• Features breathable mesh under-side.

3M™ Connected Safety ID*

• RFID technology for simplified inventory, inspection and record management.


 Tested and certified to ANSI/ASSP Z359.11 (310 lbs.) standard. Conforms to the requirements of 29 CFR OSHA 1910.140 and 1926.502. (420 lbs.) regulations.

*3M Patented Technology

3M™ DBI-SALA® ExoFit™ X300 Harness

For those who refuse to compromise.

One of the most advanced harnesses just got better. With industry-leading comfort and fit, it's optimized to help increase the performance and productivity of professionals who take pride in a job done right.



3M™ DBI-SALA® ExoFit™ X-Series Harnesses **Feature Matrix**



Feature	X100	X200	X300
Personal SRL Adapter	Molded Tunnel	Steel	Aluminum
Exclusive Weight Distribution System Models Available	√		✓
Breathable Shoulder Pads	Removable	Mesh Design	Durable Shoulder Cap Design
Leg Padding	Accessory Kit Available	✓	✓
Exclusive Automatic Stand-Up D-ring		Steel	Aluminum
Exclusive Locking Buckles Available		Dual-Locking Quick-Connect	Auto-Locking Quick-Connect
Lightweight Aluminum Hardware Models Available		✓	✓
3M [™] Scotchlite [™] Reflective Material			Padding Panels
Exclusive X-Style Quick-Connect Chest Buckle Models Available			✓

Please check our full product list to find the harnesses that best accommodate you and your team.

New ExoFit™ comfort harnesses available in a variety of styles:

- Vest Climbing
- Vest Positioning
- Vest Retrieval
- Vest Climbing/Positioning
- Vest Climbing/Positioning/Retrieval
- X-Style

- Construction
- Construction Climbing
- Construction Positioning
- Construction Climbing/Positioning
- Construction Weight Distribution Positioning
- Construction Weight Distribution Climbing/Positioning
- Tower Climbing/Positioning
- Wind Energy Vest Climbing/ Positioning
- Wind Energy Construction Climbing/Positioning
- Oil & Gas Vest Climbing/Positioning Oil & Gas Construction Climbing/
- Positioning
- Construction Mining

3M DBI-SALA ExoFit Safety Harnesses Brochure v4-1.indd 4-6