

3M DBI-SALA Fixed Beam Anchor

Model : 2108406

Product Details

- Installs onto 2-1/2 in. to 12 in. wide I-beam flange (6.3-30.5cm) up to 1-1/2" thick (3.8cm)
- Attach in any orientation or direction
- Compact and lightweight design
- High strength steel and aluminium construction
- Extremely rugged and corrosion resistant
- Swiveling D-ring tie-off point
- Detent style attachment with built-in tightening handle

Fixed beam anchor fits 2-1/2 in. to 12 in. wide I-beams (6.3-30.5cm) up to 1-1/2" thick (3.8cm).

Our anchorage connectors are built from top quality materials guaranteeing high strength and durability to stand up to the toughest environments. Anchorage connectors are the unsung heroes of most fall protection systems, often overlooked but critical components because they securely attach your system to the anchorage. Your choice of anchor depends on the type of work being done. Anchorages are sold by what they connect to (general/all purpose, steel, concrete, roof or specialty), whether they are fixed or mobile, and whether they are permanent or portable. They all must provide a secure point of attachment for a complete personal fall arrest system, and must be capable of supporting a load of 5,000 lbs. (22kN) or of meeting OSHA's criteria of a 2 to 1 safety factor.



Specifications

Anchor Install Type	Reusable
Attachment Type	Clamp
Brands	DBI-Sala
Connected Safety ID Equipped	Yes
Fits Ibeam Flange Width	2-1/2 to 12 in. (6.3-30.5cm)
Install Type	Reusable
Material	Zinc Plated Steel
Product Colour	Silver
Product Type	Fixed Beam Anchor
Recommended Industry	Construction, General Industrial, Oil & Gas, Transportation, Utilities
Weight Capacity (Metric)	190 kg

