

# 3M Protecta Self-Retracting Lifeline with Carabiner, Web, Steel Snap Hook, 11ft

**Model : 3100513**

## Product Details

- Swiveling anchorage loop and carabiner
- 11 ft. (3.3m) 1" (2.5cm) polyester web lifeline
- Self-locking snap hook on lifeline
- Compact, lightweight design
- Tough and impact resistant stackable thermoplastic housing
- Quick activating speed sensing brake system
- High capacity external energy absorber and impact indicator
- Meets ANSI Z359.14 Class B, ANSI A10.32, OSHA 1910.66, OSHA 1926.502, Capital Safety Gen. Mfg. Req.

11 ft. (3.3m) of 1" (2.5 cm) polyester web with steel snap hook, swiveling anchorage and anchorage carabiner.

Rebel self retracting lifelines (SRL) with super-tough yet lightweight composite housings are built to last providing an economical fall protection solution without compromising performance or safety. These Rebel SRL's feature a 310 pound (141 kg) user capacity, and a robust design to ensure longevity. Rebel is designed with the worker in mind, featuring a stackable space-maximizing design, high strength web lifeline and a built-in swiveling anchorage point. An SRL's lifeline will extend as the user moves away, and retract automatically enabling the user to move about within a recommended working area at normal speeds. Should a fall occur, a speed sensing brake system will activate stopping the fall and reducing the forces imposed on the user to safe levels.



Specifications	
Anchor Connection Type	Carabiner
Anchor Hook Material	Zinc Plated Steel
Brands	PROTECTA
Housing Material	Nylon Thermoplastic
Housing Type	Thermoplastic
Install Type	Portable & Removable
Leg Count	Single-Leg
Lifeline Connection Type	Snap Hook
Lifeline Hook Material	Zinc Plated Steel
Lifeline Length (Imperial)	11 ft
Lifeline Length (Metric)	3.35 m
Lifeline Material	Web
Maximum Arrest Force (Imperial)	1800 lbf (OSHA 130 lb - 310 lb)
Maximum Arrest Force (Metric)	8 kN (OSHA 130 lb - 310 lb)
Maximum Number of Users	One
Mounting Type	Overhead Anchor Point
Product Color	Red
Product Type	Self Retracting Lifeline - Web
Recommended Application	Climbing, Demolition, Inspection, Maintenance, Remediation
Recommended Industry	Construction, General Industry, General Manufacturing, Industrial, Manufacturing, Military Maintenance, Repair & Operation (MRO), Mining, Oil & Gas, Wind Energy
Specifications Met	29 CFR OSHA 1910.140, 29 CFR OSHA 1926.502
Style	Single Leg
Weight Capacity (Imperial)	310 lb.
Weight Capacity (Metric)	141 kg