

## 3M Protecta Work Positioning Trigger Lanyard, Adjustable to 2.00 m

**Model : 1200314**

### Product Details

- Trigger adjustment device
- 10.5mm Kernmantle rope material
- Snap hook connecting hook
- Triple action carabineer connection to Trigger device

Our 3M Protecta Work Positioning Trigger Lanyard, features an adjustment system giving the user the option to easily adjust the length of the lanyard during use. These lanyards have a triple action carabiner (AJ572) with a zinc-plated steel snap hook (AJ523) and are available in different lengths.

Constructed from 10.5 mm braided rope, our 3M Protecta Work Positioning Trigger Lanyards are available in a variety of lengths to suit the users need. The trigger adjustment system allows the user to easily adjust the length of the lanyard during use, even when the rope is dirty and wet. The work positioning lanyard enables the user to be partially supported on a structure or fixed ladder and use both hands to complete a task, whilst maintaining stability. All lengths feature a triple action carabiner body connector and zinc plated steel snap hook anchorage connector. The user must ensure that a suitable secondary means of fall protection is used (e.g. a fall arrest lanyard).



### Specifications

Brand	PROTECTA®
Sub Brand	Trigger
Size	Adj to 2.00m
iSafe Equipped	No
Anchor Connector Hook Type	Snap Hook
Harness Connector Hook Type	Screw Carabineer
Number Of legs	Single-Leg
Lanyard Length	Adj to 2.00m
General Lanyard	Rope
Model	1200314
Physical Weight	0.85 kg (1.9lbs)
Product Styles	Trigger Adjuster
Product Types	Work Positioning
Standards	CE, EN358

