





3M DBI-SALA Self-Closing/Triple Locking Carabiner, Stainless Steel, 2 in Gate

Model: 2000301

Product Details

- 2 in. (51mm) gate opening stainless steel carabiner
- · Self closing and locking gate for added safety
- Highly corrosion resistant stainless-steel hardware
- High strength steel construction
- User friendly compact and lightweight design

2 in. (51mm) gate opening stainless steel carabiner with self closing/locking gate.

Our anchorage connectors are built from top quality materials guaranteeing high strength and durability to stand up to the toughest environments. Anchorage connectors are the unsung heroes of most fall protection systems, often overlooked but critical components because they securely attach your system to the anchorage. Your choice of anchor depends on the type of work being done. Anchorages are sold by what they connect to (general/all purpose, steel, concrete, roof or specialty), whether they are fixed or mobile, and whether they are permanent or portable. They all must provide a secure point of attachment for a complete personal fall arrest system, and must be capable of supporting a load of 5,000 lbs. (22kN) or of meeting OSHA's criteria of a 2-to-1 safety factor



Specifications	
Attachment Type	Hook
Brands	DBI-SALA
Carabiner/Hook Material	Stainless Steel
Case Quantity	1
Connected Safety ID Equipped	No
Dimensions	6.90x3.80x0.75in
Gate Opening (Imperial)	2 in
Gate Opening (Metric)	51 mm
Install Type	Reusable
Material	Stainless Steel
Product Color	Silver
Product Series	Saflok
Product Type	Carabiner
Recommended Industry	Construction, General Industrial, Mining, Oil & Gas, Transportation, Utilities, Wind Energy
Specifications Met	OSHA 1910.140, OSHA 1926.502
Weight (Imperial)	1.4 lb.
Weight Capacity	310 lbs. (141 kg) ANSI / 420 lbs. (190 kg) OSHA
Weight Capacity (Imperial)	420 lb.
Weight Capacity (Metric)	190 kg