



QUESTemp[®] Heat Stress Monitors




Simplify your heat stress management with the intuitive QUESTemp[®] Series Heat Stress Monitors.

These monitors measure parameters including temperature and relative humidity, and compute the Wet Bulb Globe Temperature (WBGT).

Features and Benefits

- Utilizes WBGT sensing technology; the standard for heat stress management
- Proven traditional wet bulb sensing technology available on QUESTemp[®] models 32, 34 and 36
- Waterless wet bulb QUESTemp[®] models 44, 46, 48N eliminate daily maintenance
- Convenient stay time parameters per multiple standards help determine work-rest ratios
- IP 54 ingress rating helps protect unit from exposure to dirt, dust, oil and water
- Designed to withstand the rigors of everyday use in demanding environments



Market Leading Technology

QUESTemp® Models 32/34/36

With traditional wet bulb sensor

Data Logging

- QUESTemp® models 34/36 store data for future download and analysis
- Compatible with Quest Detection Management Software DMS
- Analysis of data is crucial in developing a heat stress management program



Traditional Wet Bulb

- Proven technology utilizes traditional wet bulb to calculate WBGT
- Equipped with wet bulb, dry bulb, globe and relative humidity sensors
- Provides a solid basis for determining if heat stress controls are needed

Stay Times


- QUESTemp® 36 displays stay times per ACGIH TLV, U.S. Navy PHEL charts, and U.S. Navy/Marine Corp. Ashore Flag Conditions; includes EPRI action limits
- Choose from various stay time standards to help determine work-rest ratios

Detection Management Software

Designed for dosimetry, sound level measurements, heat stress assessments and environmental monitoring, this advanced software helps safety and occupational professionals:

- Configure instrumentation and save pre-configured setups
- Retrieve, download, share, and save instrument data
- Create charts, tables, and reports to intuitively interpret your measurements
- Export and share recorded results

The software integrates with TSI® Quest Detection Solutions data logging instruments and will help you improve both operating efficiency and reporting in acoustics, heat stress and environmental monitoring.



Choose the Model That Best Meets Your Needs

QUESTemp® Models 44/46/48N

With waterless wet bulb sensor



Brilliant Waterless Wet Bulb

- Uses a proprietary algorithm to calculate the WBGT; eliminates daily wet bulb maintenance

Stay Times

- QUESTemp® models 46/48N display stay times per ACGIH TLV, U.S. Navy PHEL charts, and U.S. Navy/Marine Corp. Ashore Flag Conditions; QUESTemp® 46 includes EPRI action limits
- Choose from various stay time standards to help determine work-rest ratios

Data Logging

- QUESTemp® models 44/46/48N store data for future download and analysis
- Compatible with Quest Detection Management Software DMS
- Analysis of data is a critical step in developing a heat stress management program

Sensor Specifications

	Natural Wet Bulb Models			Waterless Wet Bulb Models		
	QT°32	QT°34	QT°36	QT°44	QT°46	QT°48N
Dry bulb sensor - 1000 Ohm platinum RTD	▪	▪	▪	▪	▪	▪
Accuracy and ranges: +/-0.5° C from 0° C to 120° C (+/-0.9° F from 32° F to 248° F)	▪	▪	▪	▪	▪	▪
Wet bulb sensor - 1000 Ohm platinum RTD	▪	▪	▪			
Accuracy and ranges: +/-0.5° C from 0° C to 120° C (+/-0.9° F from 32° F to 248° F)	▪	▪	▪			
Waterless Wet Bulb (Humidity) sensor				▪	▪	▪
Accuracy and ranges: +/-1.1° C (k=2) between 0° C and 80° C (32° F and 176° F)				▪	▪	▪
Globe sensor - 1000 Ohm platinum RTD	▪	▪	▪	▪	▪	▪
Accuracy and ranges: +/-0.5° C from 0° C to 120° C (+/-0.9° F from 32° F to 248° F)	▪	▪	▪	▪	▪	▪
Relative humidity sensor	▪	▪	▪	▪	▪	▪
Accuracy and ranges: +/-5% from 20 to 95% (non-condensing)	▪	▪	▪	▪	▪	▪

Key: ▪ Feature or Parameter of Unit
▫ Optional

Specifications

QUESTemp° Heat Stress Monitors

	Natural Wet Bulb Models			Waterless Wet Bulb Models		
	QT°32	QT°34	QT°36	QT°44	QT°46	QT°48N
Measurement Parameters						
Dry bulb, wet bulb and globe temperatures, relative humidity	■	■	■	■	■	■
WBGT (indoor) index	■	■	■	■	■	
WBGT (outdoor) index	■	■	■	■	■	■
Heat index / HUMIDEX	■	■	■	■	■	
Temperature reading: Celsius or Fahrenheit	■	■	■	■	■	■
Data logging intervals: 1, 2, 5, 10, 15, 30 or 60 minutes		■	■	■	■	■
Event logging mode						■
Display languages: Choose from English, French, German, Italian, and Spanish	■	■	■	■	■	■
Head-Torso-Ankle Weighted Average WBGT (optional with tri-sensors)	□	□	□	□	□	
Operating Temperature Range						
Sensor assembly: -5° C to 100° C (23° F to 212° F)	■	■	■	■	■	■
Electronics: -5° C to 60° C (23° F to 140° F)	■	■	■	■	■	■
Data Management						
Detection Management Software DMS		■	■	■	■	■
Output						
RS-232 serial printer / computer interface; Parallel printer interface						
Power Source Options						
9V disposable batteries (standard); hours of battery life:	140	140	140	80	80	80
NiMH rechargeable battery (must select -BATTx20 part number); hours of battery life:	300	300	300	160	160	160
AC power adaptor wall power cube (included)	■	■	■	■	■	■
Mechanical						
D-ring with lanyard attachment. Allows for hands-free monitoring						■
Tripod mount / remote sensor bar.						
Allows for up to 61 m (~200 ft) long distance measurement	■	■	■	■	■	■
IP54 water & dust ingress protection rating	■	■	■	■	■	■
Case size (including mounted sensor assembly) 23.4 x 18.3 x 7.6 cm (9.2" x 7.2" x 3")	■	■	■	■	■	■
Weight: 1.2 kg (2.6 lb) with mounted sensor assembly	■	■	■	■	■	■
CE Mark	■	■	■	■	■	■

Key: ■ Feature or Parameter of Unit
□ Optional

Specifications are subject to change without notice.

TSI and the TSI logo are registered trademarks of TSI Incorporated in the United States and may be protected under other country's trademark registrations.



TSI Incorporated - Visit our website www.tsi.com for more information.

USA	Tel: +1 800 874 2811	India	Tel: +91 80 67877200
UK	Tel: +44 149 4 459200	China	Tel: +86 10 8219 7688
France	Tel: +33 1 41 19 21 99	Singapore	Tel: +65 6595 6388
Germany	Tel: +49 241 523030		

Authorised Distributor.



Dareen Global LLC
3rd Floor, Bait Qassim Building
Behind Sultan center, Qurum
Muscat, Sultanate of Oman
Tel: +968 22700343/92803889
info@dareenglobal.com
www.dareenglobal.com